

TECHNICAL DATA SHEET

Organic pigment for coatings



Edition 01.01.2011

Pigment Yellow 97 UN8231

Identification

Chem Group:	Mono azo
C.I. No.:	11767
CAS No.:	12225-18-2
EC NO.:	235-427-3
Counter Type:	Permanenr Yellow FGL

Product Description

It has good light fastness and weather fastness



Full shade



Reduction 1:10

Application

Recommended for	industrial paint, coil coating, powder coating, solvent-based paint, water-based paint
Suggested for	Offset inks, plastics

Physical Data

Appearance	Yellow Powder	Oil absorption(ml/100g)	35-55
Density(g/cm ³)	1.5	Water soluble matter(%)	≤1.5
Moisture(%)	≤2.0	Electric Conductivity(us/cm)	≤600
pH-value	7.0-8.0		

Fastness Data

Water	5	Butyl Acetate	3
Acid	5	Benzene	4
Alkali	5	Ketone	3
Oil	4	Ethyl Alcohol	4-5
Heat Stability(°C)	180	Light Fastness	7

Note:

The above information is provided as guidelines only. It is important that the customers evaluate any product in their own resin system to determine suitability.

HUPC CHEMICAL CO.LTD

Room 301,Building B2,No.206 ZhenHua Road, HangZhou, China

Tel:0086-571-89905373

Email: info@unionpigment.com

Web Site: www.union-pigment.com